

TECHNICAL DATA SHEET

BRG151 LITHIUM-NS GLOVE

**CUT PROTECTION
LEVEL C**

**ELASTICATED
WRIST**



**SANDY
NITRILE PALM**

DESCRIPTION

With excellent grip in oily conditions, Blackrock's Lithium-NS glove gives ISO cut level C protection whilst retaining flexibility and dexterity.

SIZES

UK 7-11

STANDARDS

EN388 4X44C
EN420

KEY FEATURES

- Sandy nitrile coating for excellent oily and dry grip
- ISO Cut Level C protection
- Glass fibre and stretch fabric liner offers cut protection and excellent comfort
- Elasticated wrist for secure fit

MATERIALS

- Sandy nitrile palm
- 13 gauge nylon / stretch fit / glass fibre liner

TYPICAL INDUSTRIES


- Engineering
- Manufacturing
- Warehousing

TECHNICAL DATA SHEET

EN388



4 X 4 4 C



MARKINGS

EN 388:2016 is a European standard which specifies requirements, test methods, marking and information for protective gloves against the mechanical risk of abrasion, blade cut, tear, puncture and, if applicable, impact.

BACK OF HAND

The mechanical hazard rating can be found on the glove back of hand, along with the ISO cut level protection rating for ease of selection.

PRODUCT DETAILS

CODE	SIZE	COLOUR	BARCODES	PACKAGING
BRG15107	7/Small	Grey	5019200293469	1 pair packed into a clear polybag with user information sheet Inner pack quantity: 12 Outer carton quantity: 120
BRG15108	8/Medium	Grey	5019200293476	
BRG15109	9/Large	Grey	5019200293483	
BRG15110	10/XL	Grey	5019200293490	
BRG15111	11/2XL	Grey	5019200293506	