



SPECIFICATION FOR DRIZIT® SAFE SOAK



	0397/SS
Colour	Green
Pack Wt (gross)	7 kg
Pack Volume	30 litres
Pack Size	60 x 35 x 15 cm
Qty per pallet	70
Sorbency (pack)	12 - 19 litres

Sorbency: Lower figure test method to BS 7959-1:2004. Higher figure based on high viscosity liquid with no drain.

Composition: Fire retardant sawdust

Pack Type: Bag

Flammability: Safesoak is non-combustible. It has been independently tested at the Fire Research Centre to

BS 476: part 7:1997 (Surface Spread of Flame) and classified as Class 1 which is the best

rating.

Compatibility: May be safely used with non-aggressive aqueous solutions and liquids immiscible with water,

such as hydrocarbons, solvents, mineral oils.

Before any use in a spill situation a proper risk assessment should be carried out and all

hazardous properties of the liquid or dangerous reactions taken into account.

Fire Resistance: Will not burn in dry form.

Disposal: Used sorbents may be disposed of by landfill or incineration, in accordance with local and

national regulations, taking into account the classification of the liquid absorbed.

Safety Data: Refer to our Safety Data Sheet.

Further technical advice is available if required.

Note: All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018



